



## PRODUCT SPECIFICATION

| XF+ 1.2 COB Flip Chip Common Cathode |                                   |
|--------------------------------------|-----------------------------------|
| Product series                       | XF+                               |
| LED type                             | COB Flip Chip Common Cathode 0407 |
| Pixel Pitch (Width)                  | 1.2500                            |
| Pixel Pitch (Height)                 | 1.2500                            |
| Module resolution (W/Pixel)          | 120                               |
| Module resolution (H/Pixel)          | 135                               |
| Cabinet resolution (W/Pixel)         | 480                               |
| Cabinet resolution (H/Pixel)         | 270                               |

|   |             |
|---|-------------|
| Pixel density (pixels/m <sup>2</sup> )  | 640000      |
| Module Dimension Width (mm)   | 150.00      |
| Module Dimension Height (mm)  | 168.75      |
| Cabinet Dimension Width (mm)  | 600.00      |
| Cabinet Dimension Height (mm)   | 337.50      |
| Panel material  | Aluminum    |
| Cabinet area (m <sup>2</sup> )  | 0.20        |
| Cabinet weight (kg)   | 4.70        |
| Color processing (bit)  | 23          |
| Scan type   | Vertical    |
| Refresh Rate (Hz)   | 3840        |
| Brightness (nit)  | 800         |
| Heat Dissipation per m <sup>2</sup> at Max Brightness (BTU/m <sup>2</sup> /h) | 1433.040    |
| Optimal Horizontal Viewing Angle (°)  | 170         |
| Optimal Vertical Viewing Angle (°)  | 170         |
| AC Input Voltage (V)  | 100...240   |
| AC Input Frequency (Hz)   | 50...60     |
| Power Consumption Typical (W/m <sup>2</sup> )                                 | 210         |
| Power Consumption Maximum (W/m <sup>2</sup> )                                 | 420         |
| Storage Temperature (°C)  | -40°C~+60°C |
| Working Temperature (°C)  | -20°C~+60°C |
| IP rating (Front/Rear)  | 40          |
| Storage Humidity (RH)   | 10~60%RH    |
| Working Humidity (RH)   | 10~90%RH    |
| Lifetime Typical Value (hrs)  | 100000      |
| Cabinet installation type   | Fix         |
| Maintenance   | Front       |
| Condition   | Indoor      |



|                                      |                      |
|--------------------------------------|----------------------|
| No. of receiving cards (per cabinet) | 2                    |
| Protective coating                   | Yes                  |
| Certification                        | CE   Pantone   DICOM |